

CORING MACHINES

CDM 20 P / S

- Compact, lightweight and ergonomic design
- Three gear levels permit optimum speed selection adapted to the specific core drill diameter
- Simple, controlled operation during hand-guided core drilling using variable mountable clamping handle
- Simple, controlled operation during hand-guided core drilling using variable mountable clamping handle

MULTI-TRONIC

- Overload protection for the highest possible operating comfort and long service life
- Maximum safety due to electronic and mechanical overload coupling as well as additional thermal overload protection



CDM 33 W

- User-friendly – three gear levels permit optimum speed selection adapted to the specific core drill diameter
- Drill bit mounting with integrated spindle guard
- Electromechanical on/off switch on the control box is quick and easy to operate even in difficult situations
- The careful design of the safety clip secures the core drill in the harsh construction site environment as well as acting as a functional handle for daily transport and simple mounting on drilling stands.

MULTI-TRONIC

- Overload protection for the highest possible operating comfort and long service life
- Integrated smooth start makes operation easier when starting the drilling process
- Maximum safety due to electronic and mechanical overload coupling as well as additional thermal overload protection



TECHNISCHE DATEN	CDM 20 P	CDM 20 S
rated power	2000 W	2000 W
output power	1375 W	1375 W
voltage	230 V/50-60 Hz	230 V/50-60 Hz
rated current	9.5 A	9.5 A
speed without load	670/1450/2770 1/min.	670/1450/2770 1/min.
speed fully load	450/1050/2000 1/min.	450/1050/2000 1/min.
core drill Ø masonry max.	200 mm	200 mm
core drill Ø concrete max.	150 mm	150 mm
core bit connection	1 1/4" UNC	1 1/4" UNC
clamping collar Ø	60 mm	60 mm
dimensions (L/W/H)	468/106/297 mm	564/106/164 mm
weight	7.5 kg	7.5 kg

TECHNICAL DATA	CDM 33 W
rated power	3300 W
output power	2550 W
voltage	230 V/50-60 Hz
rated current	16 A
speed without load	360/680/1050 1/min.
speed fully load	220/420/650 1/min.
core drill Ø stationary	350/160/100 mm
core bit connection	1 1/4" UNC
drill motor holder	UNIVERSAL mounting plate
dimensions with clip (L/W/H)	541/181/194 mm
weight	13.3 kg

CORING MACHINES	NR.
CDM 20 P wet/dry, incl. carry case	3001004139
CDM 20 S wet/dry, incl. carry case	3001004304
CDM 33 W stationary with MULTI-TRONIC, wet, incl. anti-friction ring	300700303

ACCESSORIES	NR.
CDM 20 - antifriction washer (brass)	300823520
CDM 20 - centre spike 190 - 250mm	300700353
CDM 20 - centre spike 230 - 350 mm	300700354
CDM 20 - centre spike 360 - 480 mm	300700355
CDM 33 - antifriction ring	300700400
CDM 33 - water flow indicator	300700410