

MTL8MH-Y

Mobile Light Tower



Technicals

Mast height:	8 meters
Lamps:	4 x 1000 MH
Mast Lifting:	Manual system
Alternator:	Linz
Auxiliary power:	3 kVA - 230V
Engine:	Yanmar 3TNM72

MTL8MH-Y

Extended Technical Data

Light Tower Data

Maximum height	8 m
Raising	Manual
Sections	6
Rotation	340°
Electrical coiled cable	9G2,5 mmq
Electrical cable for the floodlights	H07RN-F
Maximum wind stability	110 km/h
Dimension MIN with trailer (L x W x H mm)	2690 x 1300 x 2516
Dimension MAX with trailer (L x W x H mm)	2690 x 2506 x 8000
Dry weight with trailer	770 kg
Mast lifting sytem	Manual winch
Quantity per 40 feet «High Cube» container	14



ALTERNATOR

Type	Linz
Single-phase voltage	8 kVA - 230 V
Single-phase auxiliary socket	3* kVA - 230 V - 16 A
Frequency	50/60 Hz
Cos φ	0,8
Insulation class	H
Mechanical protection	IP 23

* With lamps turned on.

ENGINE

Make / Type	Yanmar / 3TNM72
Number of cylinders	3
Displacement	904 cm ³
Power «NB intermittent»	9,9 HP
Engine speed (50/60 Hz)	1500/1800 rpm
Cooling	Liquid
Fuel	Diesel
Starting system	Electric
Specific fuel consumption	265 gr/kWh
Fuel tank capacity	80 l
Noise level	93 Lwa
Battery	12 V - 44 Ah



Magnum | a Generac Company
Via Stazione, 3 Bis
27030 Villanova d'Ardenghi (PV)
Italy