## **250MM FLOOR SCARIFIER**

**TFP260** 



# THE TFP260 IS A HEAVY DUTY MACHINE FOR MEDIUM TO LARGE JOBS.

Increased weight and power give exceptional performance for a machine in this segment.

Robust chassis construction and a heavy duty double web cutter drum ensure the TFP260 keeps working on the toughest of surface preparation jobs.

The quick lift drum mechanism gives additional control to the operator.



Dust control options available

See page 59 for our full range of vacuums

## FEATURES & BENEFITS


- 250mm cutting width
- Tough 8mm welded steel construction for added weight and strength
- Precise screw type height adjustment with quick lift drum lever for accurate working and operator control
- Angled dust port allows connection of industrial dust collector giving virtually dust free performance

#### **APPLICATIONS**

- Suitable for medium to large jobs
- Removal of hard coatings
- Levelling and removing layers of hard materials
- Removing painted lines









## 250MM FLOOR SCARIFIER

**TFP260** 

## **KEY CONSUMABLES & ACCESSORIES**

Image	Part Number	Description						
	320.7009	Tungsten Carbide Tipped Cutters  For all concrete texturing, scabbling, planing and grooving applications						
	326.3658	Star Cutters  For the removal of paint, coatings and laitance. Deck descaling						
	326.5120	<b>Beam Cutters</b> For the removal of paint, coatings, laitance, grease, dirt and ice deposits. Deck Descaling						
	320.5680	Milling Cutters  For the removal of thermoplastic road and runway markings, bituminous and rubber deposits.						
	320.4160	<b>Spacers</b> Used to create a gap in between cutters.						

<sup>-</sup> Note: Please see page 37 for detailed information on the TFP260 accessories range.

## **TECHNICAL DATA**

Model	Part Number	Weight (Kg)	Power (HP - kW)	Voltage (v)	Cycle (Hz)	Cutter Speed (RPM)	Plug Size	Cable Size (mm)	Cable Length (m)	Engine Type	Vibration Level (Aeq m/s²)
TFP260 Petrol	326.2000T	147.5	8 - 6	-	-	1850	-	-	-	Honda GX240	8.8
TFP260 400v	326.2006T	147.5	7.5 - 5.5	400	50/60	1850	16 Amp 5 pin	Min. 2.5 core	30m	-	2.4

## **DIMENSIONS**

Working Width (mm)	Length (mm)	Width (mm)	Height (mm)	Maximum Cutting Depth (mm)	Working Distance from Wall (mm)	Vacuum Take Off Diameter (mm)	
250	1010	480	1080	6	75	50	

<sup>-</sup> All part numbers specified above are for machines complete with 8 point tungsten carbide tipped (TCT) cutters. For machines requiring alternative cutting media please specify.