

POLE SCABBLER / POLE TAMPER

LPS55



THE LPS55 IS A POWERFUL LONG REACH SCABBLER FOR VERTICALLY PREPARING HARD TO REACH AREAS.

At 1.4 metres in length it allows scabbling below the reinforcement bar.

The powerful blows quickly remove concrete without damaging the underlying substrate.

FEATURES & BENEFITS

- Replaceable pin fit carbide tipped scabbling heads
- Long handle for extended reach into inaccessible areas
- Angled air inlet to direct hose away from operator
- Hand guard to protect operator

APPLICATIONS

- Heavy scabbling of hard to access areas such as below re-inforcement bars and between shuttering
- Scabbling of corners, edges and joints
- Fast removal of material
- Aggressive keying without damaging the substrate



SCABBLING CONCRETE



CONCRETE REMOVAL



TEXTURING CONCRETE

POLE SCABBLER / POLE TAMPER

LPS55

KEY CONSUMABLES & ACCESSORIES

| Image | Part Number | Description |
|---|-------------|---|
|  | 441.5359 | Scabbler Head 5 Point TCT Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings |
|  | 441.5369 | Scabbler Head 9 Point TCT Bush Pin fit - including pin Rough pitted profile, ideal for application of fresh concrete or coatings |
|  | 441.5360 | Scabbler Head Cruciform Pin fit - including pin Flatter surface profile, ideal for fast reduction of material |
|  | 450.5017 | Round Foot Compactor - 127 mm (5" Round) Pin fit |
|  | 450.5011 | Square Foot Compactor - 100 x 100mm (4" x 4") Pin fit |
|  | 450.5013 | Compactor Foot - 152 x 127mm (6" x 5") Pin fit |

| Image | Part Number | Description |
|--|-------------|--|
|  | 450.5016 | Compactor Foot - 100 x 200mm (4" x 8") Pin fit |
|  | 815.5550 | Whip Check |
|  | 859.1580 | 3/8" BSP Inline Lubricator |
|  | 458.1580 | Whip Hose & Oiler Assembly Consists of whip hose, whip check and 3/8" lubricator |
|  | 843.0752 | 3/8" Air Hose Complete with couplings 15m length |

TECHNICAL DATA

| Model | Part Number | Weight (kg) | Length (mm) | Blows per minute (BPM) | Air Consumption (lps - cfm) | Vibration Level (Aeq m/s ²) |
|-----------------------------------|-------------|-------------|-------------|------------------------|-----------------------------|---|
| LPS55 c/w 5 Point Scabbler Head | 150.5001 | 13.4 | 1392 | 1300 | 11.6 - 24.6 | 38.60 |
| LPS55 c/w 9 Point Scabbler Head | 150.5002 | 13.4 | 1392 | 1300 | 11.6 - 24.6 | 38.60 |
| LPS55 c/w 5" Round Compactor Foot | 150.5031 | 13.4 | 1392 | 1300 | 11.6 - 24.6 | 38.60 |
| LPS55 c/w 4" x 4" Compactor Foot | 150.5030 | 13.4 | 1392 | 1300 | 11.6 - 24.6 | 38.60 |
| LPS55 c/w 6" x 5" Compactor Foot | 150.5021 | 13.4 | 1392 | 1300 | 11.6 - 24.6 | 38.60 |