CONSTRUCTION SCABBLER - TRIPLE HEAD - BACK HANDLE

SC3



THE SC3 IS THE MOST POWERFUL TRIPLE HEAD SCABBLER FOR HEAVY DUTY APPLICATIONS.

The new cap design and replaceable cylinder sleeve make servicing even simpler.

FEATURES & BENEFITS

- 3 Replaceable tough carbide tipped piston for fast production and long service life
- Ergonomic back handle for easy operation or optional Vibro-Lo[™] model with a low vibration side handle
- Heavy duty cast body to suit the heaviest of applications

APPLICATIONS

- Removal of laitance
- Roughening and exposing aggregate
- Preparing joints and cracks
- Removing existing coatings
- Reduction and levelling









CONSTRUCTION SCABBLER - TRIPLE HEAD - BACK HANDLE

SC3

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	612.6000	Single Piece Cruciform Piston Flatter surface profile, ideal for fast reduction of material
	612.6010	Single Piece Bush Piston Rough pitted profile, ideal for application of fresh concrete or coatings
	446.1660	SC3 Service Kit (Cruciform Pistons) Consists of: - Valve Cap O'Ring, Valve Spring, Valve Stem, Valve Seat O'Ring, Throttle Lever, Spring Pin (1 each) - Cylinder Sleeve, Cruciform Piston, Nylon Pad, Cylinder O'Ring (3 each)
	446.1665	SC3 Service Kit (Bush Pistons) Consists of: - Valve Cap O'Ring, Valve Spring, Valve Stem, Valve Seat O'Ring, Throttle Lever, Spring Pin (1 each) - Cylinder Sleeve, Bush Piston, Nylon Pad, Cylinder O'Ring (3 each)
	815.5550	Whip Check
	859.1555	½" BSP inline lubricator
	421.3452	Whip Hose Consists of air hose 3/8" BSP claw - 2m
	458.1555	Whip Hose & Oiler Assembly Consists of whip hose, whip check and ½ lubricator

TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Working Height (mm)	Blows per minute (BPM)	Air Consumption (lps - cfm)	Noise Level (db (A))	Vibration Level (Aeq m/s²)
Triple Scabbler Back Handle Bush Hammer Head	153.6151	4.8	460	220	2800 x 3	7.5 - 16	98.5	15.52
Triple Scabbler Back Handle Cruciform Head	153.6150	4.8	460	220	2800 x 3	7.5 - 16	98.5	13.31