

REVERSIBLE COMPACTOR



Come with water tank to minimise dust and prevent asphalt from sticking to base plate.



CPT150



Optional transporting wheels



**CPT150
with option
Water Tank**



CPT200

MODEL	CPT150	CPT200	CPT300
MACHINE DIMENSION - L x W x H (mm)	1,207 x 500 x 1,118	1,239 x 600 x 1,112	1,494 x 640 x 1,218
OPERATING WEIGHT - (kg)			
DIESEL	155	197	320
PETROL	138	183	300
PLATE SIZE - L x W (mm)	650 x 500	700 x 600	800 x 470 (Extended 800 x 640)
CENTRIFUGAL FORCE - kgf (kN)	3,059 (30)	3,059 (30)	4,078 (40)
VIBRATION FREQUENCY - Hz (vpm)	90 (5,400)	90 (5,400)	70 (4,200)
COMPACTION AREA - (m ² /h)	650	759	792
MAXIMUM GRADEABILITY - (°)	25	30	30
MAXIMUM WORKING SPEED - (m/min)	22	23	22
WATER TANK CAPACITY - (litre)	26	-	-
ENGINE OPTIONS	HATZ 1B20 @ 3.5kW (4.6hp) 4-Stroke Diesel (Recoil & Electric-Start)	HATZ 1B20 @ 3.5kW (4.6hp) 4-Stroke Diesel (Recoil & Electric-Start)	HATZ 1B30 @ 5.4kW (7.3hp) 4-Stroke Diesel (Recoil & Electric-Start)
	HONDA GX160 @ 3.6kW (4.8hp) 4-Stroke Petrol	HONDA GX270 @ 6.3kW (8.5hp) 4-Stroke Petrol	HONDA GX270 @ 6.3kW (8.5hp) 4-Stroke Petrol